



Emergency Preparedness Kit

Back-Up Power With Solar, Wall and Car Charging Options

Product Specifications

IP123EP

Product Description

Innergy Power's Emergency Preparedness Kit is a unique power solution designed to meet the basic communication and lighting needs

of victims of natural disasters and blackouts as well as rescue personnel. The heart

of the Emergency Preparedness Kit is the IP1208PP Power

Pack, a 12V, 8Ah source of power that

can be recharged from the sun, from the wall or from the cigarette lighter (DC outlet) receptacle of a car or truck.

With the included wall charger, the Emergency Preparedness Kit can be kept charged so it will be ready to use immediately during a power outage. The Power Pack comes equipped with a



The Emergency Preparedness Kit is a compact, portable renewable energy source that can be recharged from the sun when power is out.

detachable cigarette lighter receptacle (DC plug) that can, when used with a car adapter cord, power/recharge a wide range of devices including cell phones, laptop PCs up to 3.5A,

two-way radios and lighting products. Power can be

provided to these devices during sustained power

outages caused by blackouts, hurricanes, earthquakes, tornados,

etc. Once the sun is

shining, the Power Pack

can be recharged with the built-in solar module, eliminating the need for gas-powered generators.

The Emergency Preparedness Kit comes equipped with a 12V halogen light that can be immediately plugged into the Power Pack to provide up to 18 hours of continuous light.



The ballistic nylon carrying case holds the Power Pack, the wall charger, the detachable DC plug, the halogen light and includes sufficient space for other essential emergency supplies like first aid kits.

Kit Includes:

IP1208PP 12V, 8Ah Power Pack
 Detachable DC outlet
 12V wall charger
 Auto (car/truck) charging cord
 12V halogen light
 Ballistic nylon carrying case

Specifications

The IP1208PP features a 12V, 800mA battery (96 watt hours) and can be recharged with either the built-in solar module or the 12VDC, 800mA wall charger (provided).

Typical Electrical Characteristics

Maximum voltage output: 13.20 DC volts
 Average full charge voltage: 13.08 volts
 Maximum battery pack power: 8Ah
 Recharge time: 16 hrs for fully discharged battery using wall charger
 Recharge time with built-in solar module: Depending upon depth of discharge it ranges from several hours to at least two days of full sun

Mechanical Characteristics

Dimensions 22 3/4" x 15" x 7/8"
 Weight 12 lbs.